

BT-2590CK

Rechargeable Lithium-Ion Battery
Batteries Rechargeable



Features

- Complies with SMBus v1.1 and SBDData v1.1
- UN/DOT 38.3 Rating: 225 Wh
- Comparable to: BB-2590/U, BT-70791A, BT-70791E, BT-70701Bx, BT-70791Cx, BT-2590, BT-2590F, and UBBL02
- Absolute state of charge indicator

Recommended Charging Platforms

Charger Part Number	Required Adaptor Part Number
BTC-70801	BTA-70903 or BTA-70899
BTC-70844	BTA-70903 or BTA-70899
BTC-70819, -1, -3	BTA-70903 or BTA-70899
BTC-70836	BTA-70841 or BTA-70820
BTC-70870, -1, -3	BTA-70841 or BTA-70820
BTC-70824-1	BTA-70782 or BTA-70781
BTC-70663	BTA-70782 or BTA-70781A
BTC-70824-2	Not Required
BTC-70791-LR, MR	Not Required
BTC-70903-LR, MRI	No Required
BTC-70822-MR	Not Required

Typical Applications

- SINGGARS & ATCS (AN/PRC-104, 119)
- FALCON (AN/PRC-138, 117)
- Robots
- Surveillance / Sensors

Technical Specifications

Dimensions	Length 110.97 mm ± 0.79 mm Width 61.44 mm ± 0.79 mm Height 126.21 mm ± 0.79 mm
Weight	1.4 kg
Nominal Voltage	28.8 V, Two (2) x 14.4 V / Section
Maximum Voltage	33.6 V, Two (2) x 16.8 V / Section
Capacity	7.5 Ah in 24V Mode 15.0 Ah in 12V Mode
Discharge	10 A maximum Continuous / Section
Pulse Discharge	18A (5 sec ON/25 sec OFF) / Section
Operating Temperature	- 20°C to + 60°C
Recommended Storage Temperature	- 40°C to + 40°C
Connector	6 Pin Floating Type per U.S. Army DWG # SC-C-179495
State of Charge Indicator	5 Segment LCDs with Constant Display
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

September 2018

All specifications are subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au