

BT-70409

Rechargeable Nickel Cadmium Battery
Batteries Rechargeable



NSN: 6140-01-063-3918



Military Part Number BB-590/U

Features

- Comparable to: BB-390A/U (BT-70290), BB-390B/U (BT-70790), BB-2590/U (BT-70791A, BT-70791E), BB-490/U, BB-690/U, and BA-5590/U

Typically Used in

- Tube-Launched, Optically Tracked, Wire-Guided Missile (TOW); Anti-Tank Guided Missile System

Recommended Charging Platforms

Charger Part Number	Required Adaptor Part Number
BTC-70844	BTA-70834
BTC-70819	BTA-70834

Technical Specifications

Dimensions	Length 112 mm Width 62 mm Height 127 mm
Weight	1.5 kg
Voltage	24.0V, Two (2) x 12V/Section
Capacity	2.2Ah in 24V Mode, 4.4Ah in 12V Mode
Operating Temperature	- 20°C to + 55°C
Recommended Storage Temperature	- 40°C to + 40°C
Connector	Floating type per U.S. Army DWG # SC-C-179495
Disposal	Battery contains Cadmium - check with local regulations for proper disposal

September 2018

All specifications are subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au