

BT-70838-2/3CV

2/3 Size SMP, Rechargeable Lithium-Ion Battery
Batteries Rechargeable




Features

- Complies with SMBus v1.1 and SBDData v1.1
- UN/DOT 38.3 Rating: 76Wh
- Comparable to: BT-70838-2/3, BT-70838-2/3A, BT-70838-2/3Bx, BT-70838, BT-70838A, BT-70838Bx, and BT-70838-1/3Bx
- Enhanced cold temperature performance
- Absolute state of charge indicator

Typical Applications

- Land Warrior System (German Soldier Modernisation Program)
- Land Warrior Programs
- Soldier Modernisation Programs



Recommended Charging Platforms

Charger Part Number	Required Adaptor Part Number
BTC-70801	BTA-70838-7
BTC-70844	BTA-70838-7
BTC-70819, -1, -3	BTA-70838-7
BTC-70838-2/3	Not Required
BTC-70838-10	BTA-70838-6
BTC-70824-1	BTA-70838S
BTC-70663	BTA-70838S
BTC-70838-1	Not Required

Technical Specifications

Dimensions	Length	143.92 ± 1.27 mm
	Width	77.04 ± 0.51 mm
	Height	23.06 ± 0.51 mm
Weight	0.39 kg	
Voltage	Nominal	10.8 V
	Maximum	12.6 V
Capacity	6.8 Ah	
Discharge	6 A maximum Continuous	
Operating Temperature	- 32°C to + 60°C	
Recommended Storage Temperature	- 40°C to + 55°C	
Connector	BT Designed Mating Connector	
State of Charge Indicator	5 segment LCD with constant display	
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)	

September 2018

All specifications are subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au