

BTA-70762-1

Power / SMBus cable

Power Accessories



NSN: 5935-01-609-0335

Features

- The BTA-70762-1 is used to mate with both SMBus contacts and the main connector for:
 - BB-2590/U (BT-70791A, BT-70791E, BT-70791Bx, BT-70791Cx)
 - BB-2557/U (BT-70757, BT-70757A, BT-70757Bx)
- RoHS Compliant (European Directive 2011/65/EU)



Related Products

BTA-70762-2	x90 SMBus Connector, Right
BTA-70762-3	x90 SMBus Connector w/ Molex Connector
BTA-70762-4	x90 SMBus Connector, Shielded
BTA-70762-5	x90 12V or 24V Discharge Connector
BTA-70762-6	x90 12V Discharge Connector
BTK-390/2590	Unassembled x90 Connector
BTK-70762	Unassembled x90 SMBus Connector



Power / SMBus Cable shown
with BB-2590/U battery
(not included)

Technical Specifications

Dimensions	
• Length	918.2 mm
• Width	59.7 mm
• Height	36.3 mm
Weight	0.17 kg
Storage Temperature	- 40°C to + 70°C
Material / Colour	ABS / Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

September 2018

All specifications are subject to change without notice

The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au

www.eylex.com.au