

BTA-70781A

Isolated BB-2590/U pass thru
Power Accessories



NSN: 5325-01-609-0355

Features

- The BTA-70781A cable allows the user to both charge a BB-2590/U or BB-2557/U battery while providing power to an x90 application simultaneously
- When connected to the solar charger and power source provides up to 1.75A to each section of the battery while the battery provides power to the application
- The output of this cable is 14.4V or 28.8V nominal depending on wiring
- The BTA-70781A cable provides the same output and pin out as the BB-2590/U and BB-2557/U batteries
- Multiple Isolated Pass Thru cables can be connected together via de daisy chain connector for increased capacity and power output



Related Products

BTC-70663	Advanced Solar Charge Controller
BTA-70781	BB-2590/U Pass Thru
BTA-70781-1	BB-2590/U Pass Thru for Jim LR Camera
BTA-70781B	BB-2590/U Isolated Pass Thru for High Power Systems

Technical Specifications

Cable Length	584 mm
Weight	0.34 kg
Operating Temperature	- 20°C to + 50°C
Storage Temperature	- 40°C to + 70°C
Material / Colour	ABS / Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

September 2018

All specifications are subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au