Power Accessories



NSN: 5940-01-501-6714

Features

- The BTA-70835 is a DC input power cable for the SPC and SPC Lite from a 24 V NATO Slave receptacle access port found on tactical vehicles of NATO countries.
- The NATO Slave cable includes a built in fuse holder, 20 Amp AGC Fuse, dust cap, and removable back cover for wiring access.



Military Part Number J-6362A/U

Related Products

| | BTC-70801 | Soldier Portable Charger |
|--|--------------|--|
| | BTC-70844 | Soldier Portable Charger, CE |
| | BTC-70819 | Soldier Portable Charger Lite |
| | BTC-70819-1 | Soldier Portable Charger Lite, EU |
| | BTC-70819-3 | Soldier Portable Charger Lite, 12 V DC |
| | PP-8498/U | Soldier Portable Charger |
| | BTA-70816 | SPC Hummer Cable Splitter |
| | BTA-70814 | SPC Hummer Cable Splitter, PP-8444A/U |
| | BTA-70835-1 | 24 V DC SPC Hummer Cable, 148 in |
| | BTA-70835-2 | 24 V DC SPC Hummer Cable, 303 in |
| | BTA-70835-99 | 24 V DC NATO Slave Connector |

Technical Specifications

| Dimensions | Cable Length | 3759 mm |
|-----------------------|---|---------|
| | PP-8444A/U Adaptor Length | 762 mm |
| | Connector Length | 102 mm |
| | Connector Width | 95 mm |
| | Connector Height | 114 mm |
| Weight | 2.16 kg | |
| Operating Temperature | - 20°C to + 50°C | |
| Storage Temperature | - 40°C to + 70°C | |
| Material / Colour | Durometer D-30 / Metal Connector / Black | |
| Disposal | Check local regulations - contains 0% Mercury | |

September 2018

