

BTA-70903

SPC Adaptor BB-2590/U Batteries
Charger Adaptors



Features

- This adaptor is a two (2) position charge adaptor for BB-2590/U batteries on SPC chargers
- The BTA-70903 adaptor will charge the Bren-Tronics BB-2590/U batteries to 33.6V (in series mode) or 16.8V (in parallel)
- The BTA-70903 when used in conjunction with the appropriate battery charger will charge one (1) or two (2) of the following batteries:
 - BB-2590/U* (BT-70791A, BT-70791BK or BT-70791CK) in 3.5 hours or less
 - BB-390/U (BT-70790) in 4 hours or less

*Additional higher capacity versions of the BB-2590/U are available and can be charged with a slightly longer charge time.

NOTE: Do not install batteries charged to 33.6V (in series mode) in equipment not rated for 33.6V operation



Related Products

BTC-70801	Soldier Portable Charger
BTC-70844	Soldier Portable Charger, CE
PP-8498/U	Soldier Portable Charger
BTC-70819	Soldier Portable Charger Lite

Technical Specifications

Dimensions	Length	89 mm
	Width	140 mm
	Height	43 mm
Weight	0.28 kg	
Operating Temperature	- 20°C to + 50°C	
Storage Temperature	- 40°C to + 70°C	
Material / Colour	Modified ABS Plastic / Tan	
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)	

September 2018

All specifications are subject to change without notice

The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au