BTC-70715-1

Desktop Charger for Falcon

Battery Chargers



Features

- Dedicated desktop charger that will charge one (1) or two (2) of the following:
 - Harris Falcon (AN/PRC-152) in 4 hours or less
- Powered from 100-240 VAC, 50/60 Hz, 10-32 VDC or 60 W maximum
- Simple solution for the user who does not require a bulk or multi-station charger
- Optional AC Power Cord configurations available
 - BTP-592212-EU (EU Terminal)
 - BTP-592212-UK (UK Terminal)
 - BTP-592212-AU (AU Terminal)



Related Products

BTA-70715	J-6878/P SPC Adaptor
BTA-70810S	AN/PRC-148/152 Solar PLUS Adaptor
BTC-70663	Advanced Solar Charger Controller
BTX-70716S	Solar Pass-Thru Adaptor for MBITR/Falcon
BTX-70716	AN/PRC-148/152 Battery Eliminator

Technical Specifications

Charger Dimensions	Length 97 mm
	Width 140 mm
	Height 66 mm
Power Supply Dimensions	Length 102 mm
	Width 51 mm
	Height 36 mm
Cable Length	1,829 mm
Weight	0.64 kg
Operating Temperature	- 20°C to + 50°C
Storage Temperature	- 40°C to + 70°C
Material / Colour	High Impact ABS / Olive Drab / Black
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

June 202

