BTC-70838-1

Desktop Charger for SMP Batteries, CE Certified

Battery Chargers



Features

- Dedicated single-station charger that will charge one (1) of the following batteries:
 - BT-70838, BT-70838A or BT-70838Bx in 7 hours or less
 - BT-70838-2/3, BT-70838-2/3A or BT-70838-2/3Bx in 5 hours or less
 - BT-70838-1/3 or BT-70838-1/3Bx in 3 hours or less
- Powered from 100-240Vac, 50/60Hz, 40W*
- Simple solution for the user who does not require a bulk or multi-station charger
- US AC Input Cable included
- CE compliant





Related Products

591680-2	AC Input Cable, Euro	
591680-3	AC Input Cable, UK	
591680-4	AC Input Cable, Australian	

Technical Specifications

Charger Dimensions	Length	77 mm	
	Width	23 mm	
	Height	30 mm	
Power Supply Dimensions	Length	118 mm	
	Width	60 mm	
	Height	37 mm	
Cable Length	762 mm		
Weight	0.27 kg		
Operating Temperature	- 20°C to + 50°C		
Storage Temperature	- 40°C to + 70°C		
Material / Colour	High impact ABS / Black		
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)		

September 201

