

# BTK-70822-MR-x Series

Medium Rate AC/DC Charger Kit – Solar Panel compatible  
**Battery Chargers**



## Features

- Dedicated single-station charger with trailer hitch input that will charge the following batteries:
  - BB-2590/U (BT-70791A, BT-70791BK or BT-70791CK) in 5.5 hours or less\*
  - BB-390B/U (BT-70790B) in 10.5 hours or less
  - BB-2557/U (BT-70757BK) in 2.5 hours or less\*
- Powered from 100–240 VAC, 3 A, 50/60 Hz
- Powered from 10–16 VDC, maximum 10 A
- Can be used with 60 W Solar Panel, 15 V (BTP-70986-1x)
- Simple solution for the user who does not require a bulk or multi-station charger.

\* Additional higher capacity versions of the BB-2590/U and BB-2557/U are available and can be charged with slightly longer charge times.



ROHS  
COMPLIANT

## Available Configurations

BTK-70822-MR-1	US Plug Adaptor
BTK-70822-MR-2	EU Plug Adaptor
BTK-70822-MR-3	UK Plug Adaptor
BTK-70844-MR-4	AU Plug Adaptor

## Related Products

BTC-70791-LR	Low Rate Battery Charger
BTC-70791-MR	Medium Rate Battery Charger
BTP-70986-1x	60 W Solar Panel, 15 V (available in Green and Tan)



## Technical Specifications

<b>Charger Dimensions</b>	Length	66 mm
	Width	53 mm
	Height	38 mm
<b>AC Power Supply Dimensions</b>	Length	130 mm
	Width	56 mm
	Height	30 mm
<b>12 VDC Power Supply Dimensions</b>	Length	160 mm
	Width	53 mm
	Height	20 mm
<b>Weight</b>	0.86 kg	
<b>Operating Temperature</b>	- 20°C to + 50°C	
<b>Storage Temperature</b>	- 40°C to + 70°C	
<b>Material / Colour</b>	Modified ABS Plastic / Black	
<b>Disposal</b>	Check local regulations (Contains 0% Mercury or Cadmium)	

June 2021

All specifications are subject to change without notice

The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au  
www.eylex.com.au