

## BTP-70791-USB2

XX90 Dual Port USB Charger

### Battery Chargers



NSN: 01-666-3902



### Features

- The BTP-70791-USB2 can be powered by batteries with an X90 connector
- Provides 5V at 2.1A and 5V at 1A, total of 3.1A
- Draws power evenly from two halves safely on batteries with two sections
- Internal protection circuitry automatically shuts down in cases of output shorts, excessive current draw, and temperature overload
- Adaptive mobile device handshake supports wide variety of devices
- Use of original charging cables ensures the best charge time

### Powered From

BB-2590/U (BT-70791A, BT-70791E, BT-70791Bx or BT-70791Cx)
BB-390B/U (BT-70790 or BT-70790B)
BB-557/U (BT-70557)
BB-2557/U (BT-70757, BT-70757A or BT-70757E)
BB-590/U (BT-70409)
BA-5590
BA-5390

### Charges

Apple® products	iPhone®, iPod®, iPad® etc
Android™ products	Phones, Tablets etc
Most USB chargeable devices	

### Technical Specifications

<b>Dimensions</b>	Length	60 mm
	Width	41 mm
	Height	32 mm
<b>Weight</b>	0.04 kg	
<b>Operating Temperature</b>	- 20°C to + 50°C	
<b>Storage Temperature</b>	- 40°C to + 70°C	
<b>Material / Colour</b>	Plastic / Black	
<b>Disposal</b>	Check local regulations (Contains 0% Mercury or Cadmium)	

September 2018

All specifications are subject to change without notice

The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au

www.eylex.com.au