

## BTP-70810-USB1

148/152 USB Charger and Battery Status Meter

### Battery Chargers



NSN: 01-672-5533

### Features

- Provides 5 V power source from AN/PRC-148 and AN/PRC-152 batteries
- Provides 5 V at 2.1 A and 5 V at 1 A, total of 3.1 A
- Built-in meter to check battery SOC
- DC input socket to allow battery charging via BTC-70810-1 charger
- Internal protection circuitry automatically shuts down in cases of output shorts, excessive current draw and temperature overload
- Adaptive mobile device handshake supports wide variety of devices



### Powered From

AN/PRC-148 MBITR Battery (BT-70716BE or BT-70716BG)

AN/PRC-152 Falcon Handheld Battery

### Charges

Apple® products iPhone®, iPod®, iPad® etc

Android™ products Phones, Tablets etc

Most USB chargeable and powered devices

### Related Products

BTC-70810-1

AC Li-Ion Battery Charger for BTP-70810-USB1

### Technical Specifications

<b>Dimensions</b>	Length	66.55 ± 0.25 mm
	Width	40.89 ± 0.25 mm
	Height	28.96 ± 0.25 mm
<b>Weight</b>	0.06 kg	
<b>Operating Temperature</b>	- 20°C to + 50°C	
<b>Storage Temperature</b>	- 40°C to + 70°C	
<b>Material / Colour</b>	Plastic / Metal Connector / Black	
<b>Disposal</b>	Check local regulations (Contains 0% Mercury or Cadmium)	

September 2018

All specifications are subject to change without notice

The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au

www.eylex.com.au