

MC-DTC-1-BRN

Universal Desktop Charger
Battery Chargers



Features

- Capable of Outputting to Multiple Standard DoD Battery Types
- Ergonomic Design
- LED Indicators for Status
- Robust Drop Resistant
- Small Footprint
- Interchangeable Charging Cups
- Dedicated USB Charging Ports
- Compliance
 - EMI: MIL-STD-461E Compliant
 - MIL-STD-810G
 - Vibration
 - Shock and Drop
 - Humidity
- Applications
 - Conformal Wearable Battery (BB-2525U)
 - 2 USB Ports for 5 V Charging



Specifications

Part Number	980135-X
External Power Supply	90 V - 264 VAC (47 - 63 Hz)
Output Voltage	6 - 18 V
Wattage (Max)	250 W
Exterior Housing	PC ABS
Operating Temperature	- 20°C to + 55°C
Storage Temperature	- 40°C to + 71°C
Charge Indicator	Status and Self-Diagnostic
Output Current	3 A Max Per Channel
Communication	SMBus v1.1, Level 2 Smart Charger
Colour	FED-STD-595, Coyote Brown 20150 and Black 37038
Chemistries	Li-Ion

September 2018

All specifications are subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au