

BT-70791JK

Rechargeable Lithium-Ion Battery
Batteries Rechargeable



Features

- Complies with SMBus v1.1 and SBDData v1.1
- UN/DOT 38.3 Rating: 225Wh
- Comparable to: BB-2590/U, BT-70791A, BT-70791E, BT-70791Bx, BT-70791Cx and BT-70791Jx
- Enhanced low temperature performance
- Designed, manufactured, and tested to MIL-PRF-32052/1 in the USA
- Absolute state of charge indicator

Typical Applications

- SINGARS and ATCS (AN/PRC-104, 119)
- FALCON (AN/PRC-138, 117)
- Robots
- Surveillance / Sensors

Recommended Charging Platforms

Charger Part Number	Required Adaptor Part Number
BTC-70801	BTA-70834 or BTA-70903
BTC-70844	BTA-70834 or BTA-70903
BTC-70819, -1, -3	BTA-70834 or BTA-70903
BTC-70836	BTA-70841 or BTA-70820
BTC-70870, -1, -3	BTA-70841 or BTA-70820
BTC-70824-1	BTA-70782 or BTA-70781
BTC-70663	BTA-70782 or BTA-70781A
BTC-70824-2	Not Required
BTC-70791-LR, MR	Not Required
BTC-70903-LR, MRI	Not Required
BTC-70822-MR	Not Required

Technical Specifications

Dimensions	Length	110.97 ± 0.79 mm
	Width	61.44 ± 0.79 mm
	Height	126.21 ± 0.79 mm
Weight	1.4 kg	
Nominal Voltage	28.8 V, Two (2) x 14.4 V / section	
Maximum Voltage	33.0 V, Two (2) x 16.5 V / section	
Capacity	7.5 Ah in 24 V Mode 15 Ah in 12 V Mode	
Discharge	10 A maximum continuous / section	
Pulse Discharge	18 A (5 sec ON/25 sec OFF) / section	
Operating Temperature	- 40°C to + 60°C	
Recommended Storage Temperature	- 40°C to + 40°C	
Connector	6 Pin Floating type per US Army DWG # SC-C-179495	
State of Charge Indicator	5 segment LCDs with constant display	
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)	



September 2018

All specifications are subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au