

BTA-70830

VMC Adaptor for MBITR Batteries
Charger Adaptors



NSN: 5940-01-494-4134

This adaptor, when used in conjunction with the appropriate battery charger, will charge the following batteries in the appropriate positions:

- Position 1: BT-70780 (BB-2800/U) in 3 hours or less
- Position 2: BT-70791A or BT-70791E (BB-2590/U) or BT-70790 (BB-390B/A) in 3.5 hours or less
- Position 3: BT-70747 (BB-2847A/U) in 3 hours or less
- Position 4-7: MBITR or BT-70716 (ALI-130) in 4 hours or less



Military Part Number J-6586/U

Recommended Charger
PP-8481B/U (BTC-70836)
BTC-70870, -"X"

Technical Specifications

Dimensions	Length	235 mm
	Width	150 mm
	Height	105 mm
Weight	0.95 kg	
Storage Temperature Range	- 40°C to + 70°C	
Case Material and Colour	Modified ABS plastic Olive drab	
Packaging	Unit Box 1 per; Master Carton 6 per;	
	Weight	6.8 kg
Disposal	Environmentally safe - contains 0% Mercury or Cadmium	

September 2018

All specifications are subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au