

MRC-185

Rover III Power Supply Battery Eliminator Power Supplies and UPS



NSN: 6130-01-539-3039

The MRC-185 eliminates the need to depend upon batteries by allowing the Rover III Multi-band receiver to operate from a wide range of DC and AC power sources.

Features

- Adaptor works with MRC-85A 6-bay charger, MRC-86A 2-bay charger and MRC-143A 3-bay charger
- Also works with MRC-135A DC/Solar charger
- Conditions one or two batteries in four hours when used with MRC-85A or MRC-86A charger/conditioners

Technical Specifications

AC Input	95 - 265 V AC 47 - 440 Hz
DC Output	26.5 VDC at 2.25 Amps
Size	Length 134.6 mm Width 96.8 mm Height 139.7 mm
Weight	1.2 kg
Operating Temperature	- 30°C to + 55°C
Storage Temperature	- 50°C to + 65°C
Operating Altitude	27,000 ft
Storage Altitude	55,000 ft
Humidity	95% relative
Tempest	Tempest compliant
EMI	MIL-STD-461
Cables Optional	PCP81-00-01 AC Power Cord PCP76-00-01 Cigarette Adaptor
Accessories Optional	PCP236-01-072 NATO Power Cable



September 2018

All specifications are subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au