

BTK-70762

Unassembled x90 SMBus connector

Power Accessories



Features

- The BTK-70762 is an assemble yourself OEM method to mate and communicate via SMBus V1.1 to the following batteries with host equipment:
 - BB-2590/U (BT-70791A, BT-70791E, BT-70791Bx, and BT-70791Cx)
 - BB-2557/U (BT-70757, BT-70757A, BT-70757G, and BT-70757Bx)
- Enables both charge and discharge with the host equipment.
- Can be used for an individual battery, or combined in series or parallel for multi-battery applications.

Related Products

BTK-390/2590	Unassembled x90 Connector
BTA-70834-3	x90 Charge/Discharge Connector
BTA-70762-1	x90 SMBus Connector, Left
BTA-70762-2	x90 SMBus Connector, Right
BTA-70762-3	x90 SMBus Connector with Molex Connector
BTA-70762-4	x90 SMBus Connector, Shielded
BTA-70762-5	x90 12 V or 24 V Discharge Connector
BTA-70762-6	x90 12 V Discharge Connector



Technical Specifications

Dimensions	Length	60 mm
	Width	42 mm
	Height	40 mm
Weight	0.05 kg	
Operating Temperature	- 20°C to + 50°C	
Storage Temperature	- 40°C to + 70°C	
Material / Colour	ABS Plastic / Black	
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)	

September 2018

All specifications are subject to change without notice
The information contained herein is for reference only and does not constitute a warranty of performance

Partnered Supplier



sales@eylex.com.au
www.eylex.com.au