BTC-70716-1

Desktop Charger for MBITR

Battery Chargers



Features

- Dedicated desktop charger that will charge one (1) or two (2) of the following:
 - MBITR (AN/PRC-148) battery in 4 hours or less
 - BT-70716BE or BT-70716BG batteries in 4 hours or less
 - Powered from 100-240 VAC, 50/60 Hz, 10-32 VDC, 60 W maximum
- Simple solution for the user who does not require a bulk or multi-station charger
- Optional AC Power Cord configurations available:
 - BTP-592212-EU (EU Terminal)
 - BTP-592212-UK (UK Terminal)
 - BTP-592212-AU (AU Terminal)



Related Products

BTA-70810	J-6588/P SPC Adaptor	
BTA-70810S	AN/PRC-148/152 Solar PLUS Adaptor	
BTC-70663	Advanced Solar Charge Controller	
BTX-70716S	Solar Pass-Thru Adaptor for MBITR/Falcon	
BTX-70716	AN/PRC-148/152 Battery Eliminator	

Technical Specifications

Charger Dimensions	
• Length	97 mm
• Width	140 mm
• Height	66 mm
Power Supply Dimensions	
• Length	102 mm
• Width	51 mm
• Height	36 mm
Cable Length	1,829 mm
Weight	0.64 kg
Operating Temperature	- 20°C to + 50°C
Storage Temperature	- 40°C to + 70°C
Material / Colour	High Impact ABS / Black / NATO Green
Disposal	Check local regulations (Contains 0% Mercury or Cadmium)

June 202

