

## BTC-70824-2

### Multi Chemistry Battery Cap Charger Solar and Wind Generation



NSN: 6130-01-606-5295

## Features

- Dedicated single-station charger that will charge the following batteries:
  - BB-2590/U (BT-70791A, BT-70791Bx or BT-70791Cx) in 5.5 hours\*
  - BB-390B/U (BT-70790B) in 12 hours
  - BB-2557/U (BT-70757Bx) in 3 hours\*
- Powered from 20 – 30 VDC, 50 W max, (or from 100 – 240 VAC using an optional AC power adaptor, or using an optional Solar Panel)\*\*
- Equipped with a two-pin “trailer hitch” connector
- Simple solution for the user who does not require a bulk or multi-station charger

\* Higher capacity versions of the BB-2590/U and BB-2557/U are available and can be charged with slightly longer charge times.

\*\* Input cables and solar panels are purchased separately



## Related Products

BTA-70671	24 V DC NATO Input
BTA-70784	DC cable with Alligator Clips
BTA-70768	X90 Scavenger
BTP-591791-3	AC/DC Power Supply
BTP-70822-3G	Solar Panel, 62 W, Green
BTP-70822-3T	Solar Panel, 62 W, Tan
BTP-70227-T	Solar Panel, 124 W, Tan

## Technical Specifications

<b>Charger Dimensions</b>	Length	84 mm
	Width	56 mm
	Height	51 mm
<b>Cable Length</b>	203 mm	
<b>Charger Security Strap Length</b>	343 mm	
<b>Weight</b>	0.17 kg	
<b>Operating Temperature</b>	- 20°C to + 50°C	
<b>Storage Temperature</b>	- 40°C to + 70°C	
<b>Material / Colour</b>	Modified ABS Plastic / Black	
<b>Disposal</b>	Check local regulations (Contains 0% Mercury or Cadmium)	

June 2021

All specifications are subject to change without notice

The information contained herein is for reference only and does not constitute a warranty of performance

## Partnered Supplier



sales@eylex.com.au  
www.eylex.com.au